




CLASSIFICATION		POWER RELAY		
MODEL		MY2	MY3	MY4
APPEARANCE				
MOUNTING & SOCKET		PYF08A PYF08A-E SM2S PY08 PY08-02	PYF11A PYF11A-E PY11 PY11-02	PYF14A PYF14A-E SY4S PY14 PY14-02
DESCRIPTION	PLUG-IN TERMINAL	MY2	MY3	MY4
	PC-BOARD TERMINAL			
	WITH LED PLUG-IN			
	WITH LED PC-BOARD			
CONTACT	CONTACT FORM	DPDT(2C)	3PDT(3C)	4PDT(4C)
	CONTACT MATERIAL	Ag Alloy		
	RATED LOAD(RESISTIVE)	7A/ 250VAC 7A/ 30VDC		
	ELECTRICAL LIFE	10 ⁵ times		
	MECHANICAL LIFE	10 ⁷ times		
COIL	RATE VOLTAGE	DC(V): 6, 12, 24, 48, 110, 120V AC(V): 6, 12, 24, 48, 110/120, 220/240V		
	POWER CONSUMPTION	DC Coil: 0.9W AC Coil: 1.0~1.3VA		
	PICKUP VOLTAGE	AC 80% Max. DC 80% Max.		
	DROPOUT VOLTAGE	AC 30% Max. DC 10% Max.		
DIELECTRIC STRENGTH	BETWEEN CONTACT & COIL	1500VAC / 1Min		
	BETWEEN CONTACT	1000VAC / 1Min		
INSULATION RESISTANCE		≥500MΩ (500VDC)		
AMBIENT TEMPERATURE		-10℃~ +55℃		
AMBIENT HUMIDITY		45~85%RH		
WEIGHT		32g	34g	35g
DIMENSIONS(mm)				
CONNECTION DIAGRAMS		